



EKO-Power EP Series 12

EP12-

Eko-Power EP series product is a general Valve Regulated Lead Acid battery with **AGM technology**. EP series batteries are widely applied to energy reservation system, traction system, starting devices, emergence system and so on.


Application

Lighting system, Security system, Electric toy, Medical equipment, Telecommunication system, Power systems, UPS, Electric tools, Hobby and so on.



General Specifications

Nominal Voltage	12 V			
Rated Capacity (25°C)	20HR 12.00AH	10HR 11.20AH	5HR 10.20AH	1HR 7.54AH
Designed Service Life	7~10 years			
Approx. Weight	3.80 Kg (8.38 lbs)±5%			
Internal Resistance	Fully charged at 25°C: 0.014 Ohm			
Self-discharge	3% of capacity declined per month at 25°C			
Charge Voltage (25°C)	Cycle use		Stand-by use	
	14.4-15.0V(-24mV/°C) Max. Current 3.60 A		13.5-13.8V (-18mV/°C) Max. Current 3.60 A	
Dimension: mm (inch)	Length	Width	Height	Total Height
	152 (5.98)	98 (3.86)	95 (3.74)	102 (4.02)




Constant Current Discharge Data (Amperes at 25 °C)

Cell Voltage	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.80	30.7	22.4	17.6	11.5	6.76	3.00	1.99	1.12	0.600
1.75	34.6	24.6	19.2	11.9	7.07	3.06	2.04	1.15	0.606
1.70	38.1	26.9	20.5	12.4	7.29	3.15	2.09	1.17	0.617
1.65	42.0	29.0	21.8	13.1	7.46	3.28	2.15	1.19	0.625
1.60	46.3	31.5	23.3	13.8	7.54	3.38	2.22	1.21	0.629


Constant Power Discharge Data (Watts at 25 °C)

Cell Voltage	5min	10min	15min	30min	45min	1h	2h	3h	5h
1.80	55.5	40.9	32.3	21.5	15.9	13.0	7.51	5.82	3.88
1.75	61.2	44.3	34.9	22.2	16.3	13.5	7.76	5.91	3.97
1.70	65.6	47.1	36.7	22.9	16.9	13.9	7.94	6.06	4.06
1.65	71.3	50.4	38.7	24.0	17.2	14.1	8.01	6.29	4.16
1.60	76.8	53.5	40.8	25.2	17.8	14.2	8.31	6.45	4.28

Discharge Characteristic (25 °C)




Number of cycles Vs. Depth of Discharge



EKO-Power



Effect of temperature on capacity



Charge Characteristic (25°C)

