

DATENBLATT


Aufschnappbares Multifunktionsrelais

Type 600XU

- 13 Funktionen
- 10 Zeitbereiche
- Auf Hutschiene aufschnappbar
- Frontale Drehknöpfe für Zeitbereich, Zeitskala und Moduseinstellungen

Technische Daten




Versorgungsspannung 20-240VAC, 12-240 VDC, AC: 50/60 Hz
 Stromverbrauch 4W max.
 Schaltleistung NO/5A, NX/3A@250 VAC
 Zeitbereiche 0,1-1 s; 0,3-3 s; 1-10 s; 3-30 s; 0,1-1 m; 0,3-3 m; 1-10 m, 3-30 m, 0,1-1 h; 0,3-3 h
 Temperatur-Bereiche Lagerung: -20 bis +75 °C; Betrieb: 0 bis +50 °C
 Schutzart IP20
 Gewicht 64 g




elmeco Handels GmbH
 Iglaseegasse 30-32
 A-1190 Wien
 Tel.: +43 /1/ 320 92 11
 Fax: +43 /1/ 320 92 13
 office@elmeco.at
 www.elmeco.at

Funktionen einstellbar:


Function: ON Delay (A)




Function: Interval (B)




Function: Cyclic Equal OFF First (C)




Function: Cyclic Equal ON First (Ci)




Function: Pulse Output (D)




Function: Delay On Break (E)




Function: Delay On Make / Break (F)




Function: Interval After Break (H)




Function: Single Shot (I)




Function: Retriggerable Single Shot (J)




Function: Latching Relay (K)



Function: Delay With Totalise (Ai)



Function: Interval With Totalise (Bi)



MULTIFUNKTIONSRELAIS 600XU

Type	Versorgungsspannung	Art.Nr.
600XU	20-240 VAC / 12-240 VDC	411170